



|            |   |       |                   |        |     |   |   |   |   |        |              |
|------------|---|-------|-------------------|--------|-----|---|---|---|---|--------|--------------|
|            |   |       |                   |        |     |   |   |   |   |        |              |
| SW-767H-AE | 1 | 3.000 | 134-35<br>#80-160 | 9 / 13 | 301 | ✓ | ✓ | ✓ | ✓ | 300 mm | max.<br>9 mm |

### SW-767H-AE

0A7634G



Single needle compound feed sewing machine equipped with side cutter and binding systems for quilts. Synchronized movement of side cutter and binding system. Includes pneumatic presser foot lifter. Dimensions of the hole for remaining cut fabric: 120x60 mm.

#### A

- Equipped with pneumatic presser foot lifter as serial equipment.

#### B

- Presser feet and fabric cutter knives.

#### C

- Binding attachment synchronized with presser foot.

### SW-767H-AE

0A7634G



Máquina de 1 aguja triple arrastre equipada con mecanismo recortador y ribeteador para la costura de edredones. Movimiento del ribeteador sincronizado con el corte. Incorpora alza prensatelas automático. Dimensiones del orificio de desguace del tejido sobrante 120x60 mm.

#### A

- Equipada con alza prensatelas neumático de serie.

#### B

- Prensatelas y cuchillas recortadoras del tejido

#### C

- Mecanismo de ribetear sincronizado con el movimiento de los prensatelas.